

## **SPECIFICATION**

### **TITLE**

**TWO-POLE SMT MINIATURE HOUSING FOR SEMICONDUCTOR COMPONENTS AND METHOD FOR THE MANUFACTURE THEREOF"**

### **BACKGROUND OF THE INVENTION**

The invention is directed to a two-pole SMT (surface mount technology) miniature housing in leadframe technique for a semiconductor component, whereby a semiconductor chip encapsulated in a housing is mounted on a leadframe part and is contacted to another leadframe part which is conducted out of the housing as a solder terminal.

In known SMT housings in leadframe technique, for example given a SOD 123 housing, the solder terminals for the semiconductor component must be punched free and bent in a specific way after the encapsulation of the semiconductor component which, for example, occurs by casting, extruding or extrusion coating. This trimming and shaping process is necessary in order to guide the solder terminals past the housing such that such SMDs (surface mounted devices) can be mounted on a printed circuit board or mother board. The chip mounting area on the leadframe in the mounted condition thereby proceeds parallel to the PCB (printed circuit board), or to the mother board.

### **SUMMARY OF THE INVENTION**

It is an object of the invention to create a SMT miniature housing for a semiconductor component that can be easily manufactured without such a trimming and shaping process, that is reliably tight and can also be further miniaturized, and that is distinguished by a high heat elimination.

In a two-pole SMT miniature housing of the type initially cited, this object is achieved in that the solder terminals, as punched parts of the leadframe, project laterally from housing sidewalls lying opposite one another at least up to the housing floor that

forms the components' mounting surface, whereby the chip mounting surface and the components' mounting surface form a right angle relative to one another.

Advantageously, the solder terminals have a thickness of approximately 0.2 mm - 0.5 mm. The SMT miniature housing is especially suited for optoelectronic semiconductor components, particularly for optosemiconductors that receive or transmit optical radiation at the side, referred to as sidelookers.

The two-pole SMT miniature housing is manufactured according to the invention such that leadframe parts serving as finished solder terminals in a leadframe are fabricated by punching, and such that the semiconductor chip is then mounted on the one leadframe part and is contacted to the other leadframe part. The semiconductor chip is encapsulated in a housing by casting, extrusion or extrusion-coating such that the right-angled legs of the finished solder terminals at two outsides of the housing lying opposite one another are conducted at least up to the floor or mounting surface thereof. The finished SMT miniature housing then only has to be punched free from the leadframe. Components manufactured in this technique are then, for example, soldered onto a PCB such that the chip mounting surface resides perpendicularly relative to the PCB.

The advantages achieved with the invention are particularly comprised in that the manufacturing step of trimming and shaping the solder terminals is eliminated in the manufacture of the SMT miniature housing and is integrated in the punching process for shaping the leadframe. The solder terminals -- in their punched form as finished component parts -- then only have to be punched free from the lead frame. Resulting therefrom is that bending stress is no longer exerted on the component and, for example, the occurrence of micro-cracks is prevented. Fewer deviations from the tolerances in the finished housing also occur since a bending of the solder terminals is no longer necessary. The dimensional accuracy of the solder terminals is thus especially improved. A corresponding leadframe shaping also makes it possible to avoid a deflashing of the terminals after their encapsulation. In particular, the dissipated power of the components can be increased by employing thicker leadframes than in known housings. Moreover,

due to the improved arrangement of chip and leadframe or solder terminals, the housing can be further miniaturized.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 shows a SMT miniature housing in a side view;

Figure 2 is a plan view onto the housing of Figure 1;

Figure 3 is another SMT miniature housing in a side view; and

Figure 4 is a plan view onto the housing of Figure 3.

### **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

The two-pole SMT miniature housing shown in Figures 1 and 2 is manufactured in a leadframe technique. A semiconductor chip is thereby mounted on a leadframe part and is contacted to a further leadframe part with a wire 4. The two leadframe parts are conducted out of the housing 2 as solder terminals 3; for example, an IRED, LED or photodiode is encapsulated in the housing 2 as chip 1. The two solder terminals 3 are punched as finished solder terminals 3 from the leadframe having the desired contours in a punching process, and therefore need no longer be shaped afterwards. After the punching process, the semiconductor chip 1 is mounted on the one leadframe part or solder terminal 3, and is then encapsulated in plastic by casting, extruding or extrusion coating. The two solder terminals 3, as punched parts of the leadframe, are thereby conducted at least up to the floor of the housing 2 that forms the components' mounting surface, and project outwardly from housing sidewalls that reside opposite one another. The chip mounting surface and the components' mounting surface or bottom surface of the housing 2 thereby describe a right angle relative to one another. The finished SMT miniature housing is then soldered onto a mother board or printed circuit board 5 such that the chip mounting surface or the surface erected by the leadframe resides perpendicularly relative to the printed circuit board 5 or relative to the PCB.

The two-pole SMT miniature housing shown in Figures 3 and 4 is employed for optoelectronic semiconductor components having side-looking emission or reception

characteristics. Such components are also referred to as sidelookers. The SMT-compatible housing is composed of the two leadframe parts that form the solder terminals 3 and that are punched from the lead frame in the desired shape. An optosemiconductor is mounted on the one leadframe part as a semiconductor chip, and is contacted to the second leadframe part or solder terminal part 3 via a bond wire 4. The chip mounting can thereby also occur on a pre-housed leadframe. In this exemplary embodiment, a space serving as reflector 7 is recessed in the housing 2, the chip 1 being cast out therein with a transparent casting resin after the mounting so that the desired sidelooker is produced. The chip mounting surface and the component's mounting surface again form a right angle with one another. The finished product, for example, can then be soldered onto a PCB or onto a printed circuit board 5 such that the chip mounting surface resides perpendicularly on the surface that is formed by the printed circuit board 5. The soldering of the SMT miniature housing to a printed circuit board 5 is indicated with the solder meniscus 6 in Figures 1 and 3.

Although various minor changes and modifications might be proposed by those skilled in the art, it will be understood that we wish to include within the scope of the patent warranted hereon all such changes and modifications as reasonably come within our contribution to the art.